

VERSION K	<b>SINTRAN III ORDER</b>	VERSION K	PAGE 1
CUSTOMER:	Teledin. TXT	DATE:	
CUSTOMER REP. :	H. Øye	PHONE:	488377
CUSTOMER NOTES:	Munchsgt 5B 0165 Oslo	MAINT. :	
SINTRAN III/VSE OR VSX:	VSE	CPU TYPE:	900
		CPU NO:	106
ISSUED BY:	DELIVERY BY MAIL/LOCAL PICKUP:	ON: 8" D (1)	LISTING: N (2)

**MASS STORAGE**

AVAILABLE SIZES:	REMOVEABLE PACKS:	30MB	70MB	75MB	
	200MB AS:	225MB-R	200MB-R	3-75MB	4-70MB-R
	FIXED DRIVES:	140MB AS:	140MB	2-70MB	
		150MB AS:	2-75MB		
		200MB AS:	200MB-F	4-70MB-F	
		450MB AS:	450MB	2-225MB	6-70MB
	PHOENIX:	30MB	60MB	90MB	

  

UNIT	0	1	2	3
CONTROL 1	.....MB .	.....MB .	.....MB .	.....MB .
CONTROL 2	.....MB .	.....MB .	.....MB .	.....MB .

AVAILABLE SIZES:	WINCHESTER DRIVES:	14MB	16MB	21MB	23MB	20MB	45MB	74MB
	HAWK:	10MB*						

  

UNIT	0	1
CONTROL 1	.....MB .	.....MB .
CONTROL 2	.....MB .	.....MB .

CONTR/UNIT	MP*	MAG-TAPES			FLOPPY DISK	
		PERTEC	CIPHER	STC	SMALL	BIG
1/						1
2/						

\*) 10-MB disk on VSE only.  
MP mag.tape on VSE only.

SYSTEM UNIT ON: ..... MB DISK

**TERMINALS (3)**

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	
B				B							B											
23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	
45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	
67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	
89	90	91	92	93	94	95	96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	
111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	RANGE: -				

- |   |   |
|---|---|
| <p>(1) BS: ON 8" FLOPPY, SINGLE-SIDED/SINGLE-DENSITY<br/>                 BD: ON 8" FLOPPY, DOUBLE-SIDED/DOUBLE-DENSITY<br/>                 S: ON 5 1/4" FLOPPY</p> <p>(3) B: TERM. WITH BACKGROUND<br/>                 R: TERM. WITHOUT BACKGROUND<br/>                 S: PRINTER TERM. WITH SPOOLING</p> | <p>(2) C: COMPLETE LISTING<br/>                 S: SYMBOL LISTING<br/>                 F: ON FLOPPY<br/>                 P: ON PAPER<br/>                 N: NO LISTING<br/>                 (DEFAULT: LISTING ON FLOPPY)</p> |
|---|---|

INPUT/OUTPUT DEVICES AND SPOOLING

HDLC DMA DRIVER / SYNC. MOD. HDLC (H/S)					PIOC		GPIB		OCTOBUS		MPM-4		BUS EXTENSION								
1	2	3	4	5	6	7	8	9	10	11	12	1-8	1-4	1-4							
H	H	S	S																		
X.21		X.25		X.29		SYNCHRONOUS MODEMS															
1-8						1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
2																					
CAMAC		UNIVERSAL DMA / VICOM INTERFACES (D / V)										FAST UDMA/VICOM OPT. FOR ND-500									
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
LINE-PRINTER		COSMOS SPOOLING		VERSATEC DMA		1-2 I/O		1-4		TELEFIX		DEVICE NUMBER FOR SPOOLING (4)									
1-4										1-7 / 16		1 2 3 4 5 6 7 8 9 10									
		X																			
EXTRA SPOOLING PROCESSES		ETHERNET																			
4		1-4																			

SYSTEM PARAMETERS

RT-PROG. -50-	SEGM. -75-	SEMAPHORE -5-	INTERNAL CHAR. -2-	DEVICE BLOCK	BATCH PROC. -1-	CX CPU	DEV. BUFF. -20-	SYMB. DEBUG.	FILE ACC. SEGM.	CONNECT TO	TERM. ACCESS DEVICE	ND-500
80	110	5	8	1	2		10	2	5	X	5	
ND-500 PROCESS	ACCOUNTING RT	I/O	NOT PANEL CLOCK	SIBAS			REMOTE JOB ENTRIES					
	X	X		1-3	1-6	1-12	1-24	HASP DMA	IBM	HONEYWELL	UNIVAC	CDC
				X				2	X	X	X	X
RT-COMMON	BACKGR. ALLOC. NO. OF BAC.	LOGGING FUNCTIONS				MON CALL	MON ADP	LAMU	READ SEGM	TPS (5)	DISK OPTIM.	
6		SWAP DISC ACCESS							X	10		
DIRECT TASK	NO. OF RT-PROGRAMS FROM DIRECT TASK	MAG-TAPE FROM DIRECT TASK		DIRECT TRANSFER ON MAG-TAPE		CONNECT DATA FIELD		EXTEND OPEN FILE TABLE				

(4) GIVE OCTAL NUMBERS, DO NOT ENTER TERMINALS HERE  
 (5) GIVE DECIMAL NUMBERS OF TERMINALS RUNNING TPS.

SOFTWARE NOTES: 8VIPS 8SREE	VERSION	GENERATED BY	DATE
	K	TWTH	4/12-86
	W	TWTH	27/387